
FLOOD INSURANCE STUDY

FEDERAL EMERGENCY MANAGEMENT AGENCY

VOLUME 1 OF 1



WHEATLAND COUNTY, MONTANA

AND INCORPORATED AREAS

COMMUNITY NAME	COMMUNITY NUMBER
HARLOWTON, CITY OF	300175
JUDITH GAP, TOWN OF*	300136
WHEATLAND COUNTY UNINCORPORATED AREAS	300172

^{*}No Special Flood Hazard Areas Identified



EFFECTIVE:

[TBD]

REVISED PRELIMINARY 03/26/2021

FLOOD INSURANCE STUDY NUMBER 30107CV000A Version Number 2.3.3.2

TABLE OF CONTENTS

Volume 1

		<u>Page</u>
SEC	CTION 1.0 – INTRODUCTION	1
1.1	The National Flood Insurance Program	1
1.2	Purpose of this Flood Insurance Study Report	2
1.3	Jurisdictions Included in the Flood Insurance Study Project	2
1.4	Considerations for using this Flood Insurance Study Report	4
SEC	CTION 2.0 – FLOODPLAIN MANAGEMENT APPLICATIONS	14
2.1	Floodplain Boundaries	14
2.2	Floodways	16
2.3	Base Flood Elevations	17
	Non-Encroachment Zones	18
2.5	Coastal Flood Hazard Areas	18
	2.5.1 Water Elevations and the Effects of Waves	18
	2.5.2 Floodplain Boundaries and BFEs for Coastal Areas	18
	2.5.3 Coastal High Hazard Areas	18
	2.5.4 Limit of Moderate Wave Action	18
SEC	CTION 3.0 – INSURANCE APPLICATIONS	19
3.1	National Flood Insurance Program Insurance Zones	19
SEC	CTION 4.0 – AREA STUDIED	19
4.1	Basin Description	19
4.2	Principal Flood Problems	20
4.3		20
4.4	Levees	21
SEC	CTION 5.0 – ENGINEERING METHODS	21
5.1	Hydrologic Analyses	21
5.2	Hydraulic Analyses	23
5.3	Coastal Analyses	26
	5.3.1 Total Stillwater Elevations	26
	5.3.2 Waves	26
	5.3.3 Coastal Erosion	26
	5.3.4 Wave Hazard Analyses	26
5.4	Alluvial Fan Analyses	27
SEC	CTION 6.0 – MAPPING METHODS	27
6.1	Vertical and Horizontal Control	27
6.2	Base Map	28
6.3	Floodplain and Floodway Delineation	28
6.4	Coastal Flood Hazard Mapping	35
6.5	FIRM Revisions	35
	6.5.1 Letters of Map Amendment	35

 6.5.2 Letters of Map Revision Based on Fill 6.5.3 Letters of Map Revision 6.5.4 Physical Map Revisions 6.5.5 Contracted Restudies 6.5.6 Community Map History 	35 36 36 37 37
SECTION 7.0 – CONTRACTED STUDIES AND COMMUNITY COORDINATION 7.1 Contracted Studies 7.2 Community Meetings	38 38 39
SECTION 8.0 – ADDITIONAL INFORMATION	41
SECTION 9.0 – BIBLIOGRAPHY AND REFERENCES	42
<u>Figures</u>	<u>Page</u>
Figure 1: FIRM Index Figure 2: FIRM Notes to Users Figure 3: Map Legend for FIRM Figure 4: Floodway Schematic Figure 5: Wave Runup Transect Schematic Figure 6: Coastal Transect Schematic Figure 7: Frequency Discharge-Drainage Area Curves Figure 8: 1% Annual Chance Total Stillwater Elevations for Coastal Areas Figure 9: Transect Location Map	6 7 10 17 18 18 22 26 26
<u>Tables</u>	<u>Page</u>
Table 1: Listing of NFIP Jurisdictions Table 2: Flooding Sources Included in this FIS Report Table 3: Flood Zone Designations by Community Table 4: Basin Characteristics Table 5: Principal Flood Problems Table 6: Historic Flooding Elevations Table 7: Non-Levee Flood Protection Measures Table 8: Levees Table 9: Summary of Discharges Table 10: Summary of Non-Coastal Stillwater Elevations Table 11: Stream Gage Information used to Determine Discharges Table 12: Summary of Hydrologic and Hydraulic Analyses Table 13: Roughness Coefficients Table 14: Summary of Coastal Analyses Table 15: Tide Gage Analysis Specifics Table 16: Coastal Transect Parameters	2 15 19 19 20 21 21 22 23 24 26 26 26 26

Table 17: Summary of Alluvial Fan Analyses	27
Table 18: Results of Alluvial Fan Analyses	27
Table 19: Countywide Vertical Datum Conversion	27
Table 20: Stream-Based Vertical Datum Conversion	27
Table 21: Base Map Sources	28
Table 22: Summary of Topographic Elevation Data used in Mapping	29
Table 23: Floodway Data	30
Table 24: Flood Hazard and Non-Encroachment Data for Selected Streams	35
Table 25: Summary of Coastal Transect Mapping Considerations	35
Table 26: Incorporated Letters of Map Change	36
Table 27: Community Map History	38
Table 28: Summary of Contracted Studies Included in this FIS Report	38
Table 29: Community Meetings	40
Table 30: Map Repositories	41
Table 31: Additional Information	41
Table 32: Bibliography and References	43

Volume 1

Exhibits

Antelope Overflow 05 F Harlowton Overflow Channel 06-08 F Musselshell River 09-45 F	Flood Profiles	<u>Panel</u>
Harlowton Overflow Channel 06-08 F Musselshell River 09-45 F	Antelope Creek	01-04 P
Musselshell River 09-45 I	Antelope Overflow	05 P
	Harlowton Overflow Channel	06-08 P
Railroad Split 46	Musselshell River	09-45 P
	Railroad Split	46 P

Published Separately

Flood Insurance Rate Map (FIRM)

FLOOD INSURANCE STUDY REPORT WHEATLAND COUNTY, MONTANA

SECTION 1.0 – INTRODUCTION

1.1 The National Flood Insurance Program

The National Flood Insurance Program (NFIP) is a voluntary Federal program that enables property owners in participating communities to purchase insurance protection against losses from flooding. This insurance is designed to provide an alternative to disaster assistance to meet the escalating costs of repairing damage to buildings and their contents caused by floods.

For decades, the national response to flood disasters was generally limited to constructing flood-control works such as dams, levees, sea-walls, and the like, and providing disaster relief to flood victims. This approach did not reduce losses nor did it discourage unwise development. In some instances, it may have actually encouraged additional development. To compound the problem, the public generally could not buy flood coverage from insurance companies, and building techniques to reduce flood damage were often overlooked.

In the face of mounting flood losses and escalating costs of disaster relief to the general taxpayers, the U.S. Congress created the NFIP. The intent was to reduce future flood damage through community floodplain management ordinances, and provide protection for property owners against potential losses through an insurance mechanism that requires a premium to be paid for the protection.

The U.S. Congress established the NFIP on August 1, 1968, with the passage of the National Flood Insurance Act of 1968. The NFIP was broadened and modified with the passage of the Flood Disaster Protection Act of 1973 and other legislative measures. It was further modified by the National Flood Insurance Reform Act of 1994 and the Flood Insurance Reform Act of 2004. The NFIP is administered by the Federal Emergency Management Agency (FEMA), which is a component of the Department of Homeland Security (DHS).

Participation in the NFIP is based on an agreement between local communities and the Federal Government. If a community adopts and enforces floodplain management regulations to reduce future flood risks to new construction and substantially improved structures in Special Flood Hazard Areas (SFHAs), the Federal Government will make flood insurance available within the community as a financial protection against flood losses. The community's floodplain management regulations must meet or exceed criteria established in accordance with Title 44 Code of Federal Regulations (CFR) Part 60, *Criteria for Land Management and Use*.

SFHAs are delineated on the community's Flood Insurance Rate Maps (FIRMs). Under the NFIP, buildings that were built before the flood hazard was identified on the community's FIRMs are generally referred to as "Pre-FIRM" buildings. When the NFIP was created, the U.S. Congress recognized that insurance for Pre-FIRM buildings would be prohibitively expensive if the premiums were not subsidized by the Federal

Government. Congress also recognized that most of these floodprone buildings were built by individuals who did not have sufficient knowledge of the flood hazard to make informed decisions. The NFIP requires that full actuarial rates reflecting the complete flood risk be charged on all buildings constructed or substantially improved on or after the effective date of the initial FIRM for the community or after December 31, 1974, whichever is later. These buildings are generally referred to as "Post-FIRM" buildings.

1.2 Purpose of this Flood Insurance Study Report

This Flood Insurance Study (FIS) Report revises and updates information on the existence and severity of flood hazards for the study area. The studies described in this report developed flood hazard data that will be used to establish actuarial flood insurance rates and to assist communities in efforts to implement sound floodplain management.

In some states or communities, floodplain management criteria or regulations may exist that are more restrictive than the minimum Federal requirements. Contact your State NFIP Coordinator to ensure that any higher State standards are included in the community's regulations.

1.3 Jurisdictions Included in the Flood Insurance Study Project

This FIS Report covers the entire geographic area of Wheatland County, Montana.

The jurisdictions that are included in this project area, along with the Community Identification Number (CID) for each community and the United States Geological Survey (USGS) 8-digit Hydrologic Unit Code (HUC-8) sub-basins affecting each, are shown in Table 1. The FIRM panel numbers that affect each community are listed. If the flood hazard data for the community is not included in this FIS Report, the location of that data is identified.

Jurisdictions that have no identified SFHAs as of the effective date of this study are indicated in the table. Changed conditions in these communities (such as urbanization or annexation) or the availability of new scientific or technical data about flood hazards could make it necessary to determine SFHAs in these jurisdictions in the future.

Table 1: Listing of NFIP Jurisdictions

Community	CID	HUC-8 Sub-Basin(s)	Located on FIRM Panel(s)	If Not Included, Location of Flood Hazard Data
Harlowton, City of	300175	10040201	30107C0528C ² 30107C0529C 30107C0536C 30107C0537C	
Judith Gap, Town of ¹	300136	10040201	30107C0150C ² 30107C0175C ²	

Table 1: Listing of NFIP Jurisdictions (continued)

	1		,	W.N I. I. I. I.
				If Not Included,
0	OID	HUC-8	Located on	Location of Flood
Community	CID	Sub-Basin(s)	FIRM Panel(s)	Hazard Data
			30107C0025C ²	
			30107C0050C ²	
			30107C0030C	
			30107C0073C	
			30107C0100C	
			30107C0125C	
			30107C0130C	
			30107C0173C ²	
			30107C0225C ² 30107C0250C ²	
			30107C0275C ² 30107C0300C ²	
			30107C0325C ²	
			30107C0350C ²	
			30107C0375C ²	
			30107C0400C ²	
			30107C0425C ²	
			30107C0450C	
			30107C0475C	
			30107C0500C	
Wheatland County	200470	10040103,	30107C0505C ²	
Unincorporated Areas	300172	10040201	30107C0509C 30107C0510C	
			30107C0510C 30107C0515C ²	
			30107C0515C	
			30107C0517C	
			30107C0520C	
			30107C0528C	
			30107C0529C 30107C0530C	
			30107C0533C	
			30107C0535C 30107C0535C	
			30107C0535C	
			30107C0537C	
			30107C0540C ²	
			30107C0541C	
			30107C0545C	
			30107C0565C	
			30107C0570C	
			30107C0575C ²	
			30107C0580C ²	
			30107C0585C	
			30107C0590C	
			30107C0595C ²	

Table 1: Listing of NFIP Jurisdictions (continued)

Community	CID	HUC-8 Sub-Basin(s)	Located on FIRM Panel(s)	If Not Included, Location of Flood Hazard Data
Wheatland County Unincorporated Areas (continued)	300172	10040103, 10040201	30107C0605C 30107C0625C ² 30107C0650C ² 30107C0675C ² 30107C0700C 30107C0750C ² 30107C0750C ² 30107C0775C ² 30107C0780C 30107C0785C 30107C0800C ² 30107C0810C 30107C0815C 30107C0850C ² 30107C0950C ² 30107C0950C ² 30107C0950C ² 30107C0950C ² 30107C1000C ² 30107C1000C ²	

¹ No Special Flood Hazard Areas Identified

1.4 Considerations for using this Flood Insurance Study Report

The NFIP encourages State and local governments to implement sound floodplain management programs. To assist in this endeavor, each FIS Report provides floodplain data, which may include a combination of the following: 10-, 4-, 2-, 1-, and 0.2-percent annual chance flood elevations (the 1-percent-annual-chance flood elevation is also referred to as the Base Flood Elevation (BFE)); delineations of the 1-percent-annual-chance and 0.2-percent-annual-chance floodplains; and 1-percent-annual-chance floodway. This information is presented on the FIRM and/or in many components of the FIS Report, including Flood Profiles, Floodway Data tables, Summary of Non-Coastal Stillwater Elevations tables, and Coastal Transect Parameters tables (not all components may be provided for a specific FIS).

This section presents important considerations for using the information contained in this FIS Report and the FIRM, including changes in format and content. Figures 1, 2, and 3 present information that applies to using the FIRM with the FIS Report.

 Part or all of this FIS Report may be revised and republished at any time. In addition, part of this FIS Report may be revised by a Letter of Map Revision

² Panel Not Printed

(LOMR), which does not involve republication or redistribution of the FIS Report. Refer to Section 6.5 of this FIS Report for information about the process to revise the FIS Report and/or FIRM.

It is, therefore, the responsibility of the user to consult with community officials by contacting the community repository to obtain the most current FIS Report components. Communities participating in the NFIP have established repositories of flood hazard data for floodplain management and flood insurance purposes. Community map repository addresses are provided in Table 30, "Map Repositories," within this FIS Report.

 New FIS Reports are frequently developed for multiple communities, such as entire counties. A countywide FIS Report incorporates previous FIS Reports for individual communities and the unincorporated area of the county (if not jurisdictional) into a single document and supersedes those documents for the purposes of the NFIP.

The initial Countywide FIS Report for Wheatland County became effective on [TBD]. Refer to Table 27 for information about subsequent revisions to the FIRMs.


 Selected FIRM panels for the community may contain information (such as floodways and cross sections) that was previously shown separately on the corresponding Flood Boundary and Floodway Map (FBFM) panels. In addition, former flood hazard zone designations have been changed as follows:

Old Zone	New Zone
A1 through A30	AE
V1 through V30	VE
В	X (shaded)
С	X (unshaded)


- The CRS is a voluntary incentive program that recognizes and encourages community floodplain management activities that exceed the minimum NFIP requirements. Visit the FEMA Web site at www.fema.gov/national-flood-insurance-program-community-rating-system or contact your appropriate FEMA Regional Office for more information about this program.
- FEMA has developed a *Guide to Flood Maps* (FEMA 258) and online tutorials to assist users in accessing the information contained on the FIRM. These include how to read panels and step-by-step instructions to obtain specific information. To obtain this guide and other assistance in using the FIRM, visit the FEMA Web site at www.fema.gov/online-tutorials.

The FIRM Index in Figure 1 shows the overall FIRM panel layout within Wheatland County, and also displays the panel number and effective date for each FIRM panel in the county. Other information shown on the FIRM Index includes community boundaries, watershed boundaries, and USGS HUC-8 codes.

Figure 1: FIRM Index



ATTENTION: The corporate limits shown on this FIRM Index are based on the best information available at the time of publication. As such, they may be more current than those shown on FIRM panels issues before TBD.




Map Projection: NAD 1983 StatePlane Montana FIPS 2500; Western Hemisphere; Vertical Datum: NAVD 88

DOCUMENTATION ARE ALSO AVAILABLE IN DIGITAL FORMAT AT

SEE FLOOD INSURANCE STUDY FOR ADDITIONAL INFORMATION * PANEL NOT PRINTED - AREAS ALL IN ZONE D

THE INFORMATION DEPICTED ON THIS MAP AND SUPPORTING HTTPS://MSC.FEMA.GOV



NATIONAL FLOOD INSURANCE PROGRAM FLOOD INSURANCE RATE MAP INDEX

WHEATLAND COUNTY, MONTANA and Incorporated Areas

PANELS PRINTED:

0450, 0475, 0500, 0509, 0510, 0517, 0520, 0529, 0530, 0533, 0535, 0536, 0537, 0541, 0545, 0565, 0570, 0585, 0590, 0605, 0700, 0780, 0785, 0805, 0810, 0815, 0820

> **REVISED PRELIMINARY** 03/26/2021



MAP NUMBER 30107CIND0A **EFFECTIVE DATE**

Each FIRM panel may contain specific notes to the user that provide additional information regarding the flood hazard data shown on that map. However, the FIRM panel does not contain enough space to show all the notes that may be relevant in helping to better understand the information on the panel. Figure 2 contains the full list of these notes.

Figure 2: FIRM Notes to Users

NOTES TO USERS

For information and questions about this map, available products associated with this FIRM including historic versions of this FIRM, how to order products, or the National Flood Insurance Program in general, please call the FEMA Mapping and Insurance eXchange at 1-877-FEMA-MAP (1-877-336-2627) or visit the FEMA Flood Map Service Center website at msc.fema.gov. Available products may include previously issued Letters of Map Change, a Flood Insurance Study Report, and/or digital versions of this map. Many of these products can be ordered or obtained directly from the website. Users may determine the current map date for each FIRM panel by visiting the FEMA Flood Map Service Center website or by calling the FEMA Mapping and Insurance eXchange.

Communities annexing land on adjacent FIRM panels must obtain a current copy of the adjacent panel as well as the current FIRM Index. These may be ordered directly from the Flood Map Service Center at the number listed above.

For community and countywide map dates, refer to Table 27 in this FIS Report.

To determine if flood insurance is available in the community, contact your insurance agent or call the National Flood Insurance Program at 1-800-638-6620.

<u>PRELIMINARY FIS REPORT</u>: FEMA maintains information about map features, such as street locations and names, in or near designated flood hazard areas. Requests to revise information in or near designated flood hazard areas may be provided to FEMA during the community review period, at the final Consultation Coordination Officer's meeting, or during the statutory 90-day appeal period. Approved requests for changes will be shown on the final printed FIRM.

The map is for use in administering the NFIP. It may not identify all areas subject to flooding, particularly from local drainage sources of small size. Consult the community map repository to find updated or additional flood hazard information.

BASE FLOOD ELEVATIONS: For more detailed information in areas where Base Flood Elevations (BFEs) and/or floodways have been determined, consult the Flood Profiles and Floodway Data and/or Summary of Non-Coastal Stillwater Elevations tables within this FIS Report. Use the flood elevation data within the FIS Report in conjunction with the FIRM for construction and/or floodplain management.

<u>FLOODWAY INFORMATION</u>: Boundaries of the floodways were computed at cross sections and interpolated between cross sections. The floodways were based on hydraulic considerations with regard to requirements of the National Flood Insurance Program. Floodway widths and other pertinent floodway data are provided in the FIS Report for this jurisdiction.

Figure 2. FIRM Notes to Users

<u>FLOOD CONTROL STRUCTURE INFORMATION</u>: Certain areas not in Special Flood Hazard Areas may be protected by flood control structures. Refer to Section 4.3 "Non-Levee Flood Protection Measures" of this FIS Report for information on flood control structures for this jurisdiction.

<u>PROJECTION INFORMATION</u>: The projection used in the preparation of the map was North American Datum of 1983 (NAD 1983) State Plane Montana FIPS 2500. Differences in datum, spheroid, projection or State Plane zones used in the production of FIRMs for adjacent jurisdictions may result in slight positional differences in map features across jurisdiction boundaries. These differences do not affect the accuracy of the FIRM.

<u>ELEVATION DATUM</u>: Flood elevations on the FIRM are referenced to the North American Vertical Datum of 1988. These flood elevations must be compared to structure and ground elevations referenced to the same vertical datum. For information regarding conversion between the National Geodetic Vertical Datum of 1929 and the North American Vertical Datum of 1988, visit the National Geodetic Survey website at www.ngs.noaa.gov.

Local vertical monuments may have been used to create the map. To obtain current monument information, please contact the appropriate local community listed in Table 30 of this FIS Report.

<u>BASE MAP INFORMATION</u>: Base map information shown on the FIRM was provided by Montana State Library, Federal Emergency Management Agency, and the National Agriculture Imagery Program (NAIP). Ortho imagery was provided by NAIP in 2013, and has a 1 meter ground resolution. For information about base maps, refer to Section 6.2 "Base Map" in this FIS Report.

The map reflects more detailed and up-to-date stream channel configurations than those shown on the previous FIRM for this jurisdiction. The floodplains and floodways that were transferred from the previous FIRM may have been adjusted to conform to these new stream channel configurations. As a result, the Flood Profiles and Floodway Data tables may reflect stream channel distances that differ from what is shown on the map.

Corporate limits shown on the map are based on the best data available at the time of publication. Because changes due to annexations or de-annexations may have occurred after the map was published, map users should contact appropriate community officials to verify current corporate limit locations.

NOTES FOR FIRM INDEX

<u>REVISIONS TO INDEX</u>: As new studies are performed and FIRM panels are updated within Wheatland County, Montana, corresponding revisions to the FIRM Index will be incorporated within the FIS Report to reflect the effective dates of those panels. Please refer to Table 27 of this FIS Report to determine the most recent FIRM revision date for each community. The most recent FIRM panel effective date will correspond to the most recent index date.

SPECIAL NOTES FOR SPECIFIC FIRM PANELS

This Notes to Users section was created specifically for Wheatland County, Montana, effective [TBD].


Figure 2. FIRM Notes to Users

<u>FLOOD RISK REPORT</u>: A Flood Risk Report (FRR) may be available for many of the flooding sources and communities referenced in this FIS Report. The FRR is provided to increase public awareness of flood risk by helping communities identify the areas within their jurisdictions that have the greatest risks. Although non-regulatory, the information provided within the FRR can assist communities in assessing and evaluating mitigation opportunities to reduce these risks. It can also be used by communities developing or updating flood risk mitigation plans. These plans allow communities to identify and evaluate opportunities to reduce potential loss of life and property. However, the FRR is not intended to be the final authoritative source of all flood risk data for a project area; rather, it should be used with other data sources to paint a comprehensive picture of flood risk.

Each FIRM panel contains an abbreviated legend for the features shown on the maps. However, the FIRM panel does not contain enough space to show the legend for all map features. Figure 3 shows the full legend of all map features. Note that not all of these features may appear on the FIRM panels in Wheatland County.

Figure 3: Map Legend for FIRM

SPECIAL FLOOD HAZARD AREAS: The 1% annual chance flood, also known as the base flood or 100-year flood, has a 1% chance of happening or being exceeded each year. Special Flood Hazard Areas are subject to flooding by the 1% annual chance flood. The Base Flood Elevation is the water surface elevation of the 1% annual chance flood. The floodway is the channel of a stream plus any adjacent floodplain areas that must be kept free of encroachment so that the 1% annual chance flood can be carried without substantial increases in flood heights. See note for specific types. If the floodway is too narrow to be shown, a note is shown.



- Zone A The flood insurance rate zone that corresponds to the 1% annual chance floodplains. No base (1% annual chance) flood elevations (BFEs) or depths are shown within this zone.
- Zone AE The flood insurance rate zone that corresponds to the 1% annual chance floodplains. Base flood elevations derived from the hydraulic analyses are shown within this zone.
- Zone AH The flood insurance rate zone that corresponds to the areas of 1% annual chance shallow flooding (usually areas of ponding) where average depths are between 1 and 3 feet. Whole-foot BFEs derived from the hydraulic analyses are shown at selected intervals within this zone.
- Zone AO The flood insurance rate zone that corresponds to the areas of 1% annual chance shallow flooding (usually sheet flow on sloping terrain) where average depths are between 1 and 3 feet. Average whole-foot depths derived from the hydraulic analyses are shown within this zone.
- Zone AR The flood insurance rate zone that corresponds to areas that were formerly protected from the 1% annual chance flood by a flood control system that was subsequently decertified. Zone AR indicates that the former flood control system is being restored to provide protection from the 1% annual chance or greater flood.
- Zone A99 The flood insurance rate zone that corresponds to areas of the 1% annual chance floodplain that will be protected by a Federal flood protection system where construction has reached specified statutory milestones. No base flood elevations or flood depths are shown within this zone.
 - Zone V The flood insurance rate zone that corresponds to the 1% annual chance coastal floodplains that have additional hazards associated with storm waves. Base flood elevations are not shown within this zone.
- Zone VE Zone VE is the flood insurance rate zone that corresponds to the 1% annual chance coastal floodplains that have additional hazards associated with storm waves. Base flood elevations derived from the coastal analyses are shown within this zone as static whole-foot elevations that apply throughout the zone.




Figure 3: Map Legend for FIRM

OTHER AREAS OF FLOOD HAZARD Shaded Zone X: Areas of 0.2% annual chance flood hazards and areas of 1% annual chance flood hazards with average depths of less than 1 foot or with drainage areas less than 1 square mile. Future Conditions 1% Annual Chance Flood Hazard – Zone X: The flood insurance rate zone that corresponds to the 1% annual chance floodplains that are determined based on future-conditions hydrology. No base flood elevations or flood depths are shown within this zone. Area with Reduced Flood Risk due to Levee: Areas where an accredited levee, dike, or other flood control structure has reduced the flood risk from the 1% annual chance flood. Area with Flood Risk due to Levee: Areas where a non-accredited levee, dike, or other flood control structure is shown as providing protection to less than the 1% annual chance flood. **OTHER AREAS** Zone D (Areas of Undetermined Flood Hazard): The flood insurance rate zone that corresponds to unstudied areas where flood hazards are undetermined, but possible. **NO SCREEN** Unshaded Zone X: Areas of minimal flood hazard. FLOOD HAZARD AND OTHER BOUNDARY LINES Flood Zone Boundary (white line on ortho-photography-based mapping; gray line on vector-based mapping) (ortho) (vector) Limit of Study Jurisdiction Boundary Limit of Moderate Wave Action (LiMWA): Indicates the inland limit of the area affected by waves greater than 1.5 feet GENERAL STRUCTURES Aqueduct Channel Channel, Culvert, Aqueduct, or Storm Sewer Culvert Storm Sewer Dam Dam, Jetty, Weir Jetty Weir Levee, Dike, or Floodwall **Bridge** Bridge

Figure 3: Map Legend for FIRM

REFERENCE MARKERS	S
22.0 •	River mile Markers
CROSS SECTION & TRA	ANSECT INFORMATION
B 20.2	Lettered Cross Section with Regulatory Water Surface Elevation (BFE)
<u>5280</u> <u>21.1</u>	Numbered Cross Section with Regulatory Water Surface Elevation (BFE)
17.5	Unlettered Cross Section with Regulatory Water Surface Elevation (BFE)
8	Coastal Transect
	Profile Baseline: Indicates the modeled flow path of a stream and is shown on FIRM panels for all valid studies with profiles or otherwise established base flood elevation.
	Coastal Transect Baseline: Used in the coastal flood hazard model to represent the 0.0-foot elevation contour and the starting point for the transect and the measuring point for the coastal mapping.
~~~~ 513 ~~~~	Base Flood Elevation Line
ZONE AE (EL 16)	Static Base Flood Elevation value (shown under zone label)
ZONE AO (DEPTH 2)	Zone designation with Depth
ZONE AO (DEPTH 2) (VEL 15 FPS)	Zone designation with Depth and Velocity
BASE MAP FEATURES  Missouri Creek	River, Stream or Other Hydrographic Feature
234)	Interstate Highway
234	U.S. Highway
(234)	State Highway
234	County Highway
MAPLE LANE	Street, Road, Avenue Name, or Private Drive if shown on Flood Profile
RAILROAD	Railroad

Figure 3: Map Legend for FIRM

	Horizontal Reference Grid Line
_	Horizontal Reference Grid Ticks
+	Secondary Grid Crosshairs
Land Grant	Name of Land Grant
7	Section Number
R. 43 W. T. 22 N.	Range, Township Number
⁴² 76 ^{000m} E	Horizontal Reference Grid Coordinates (UTM)
365000 FT	Horizontal Reference Grid Coordinates (State Plane)
80° 16' 52.5"	Corner Coordinates (Latitude, Longitude)

#### **SECTION 2.0 – FLOODPLAIN MANAGEMENT APPLICATIONS**

#### 2.1 Floodplain Boundaries

To provide a national standard without regional discrimination, the 1-percent-annual-chance (100-year) flood has been adopted by FEMA as the base flood for floodplain management purposes. The 0.2-percent-annual-chance (500-year) flood is employed to indicate additional areas of flood hazard in the community.

Each flooding source included in the project scope has been studied and mapped using professional engineering and mapping methodologies that were agreed upon by FEMA and Wheatland County as appropriate to the risk level. Flood risk is evaluated based on factors such as known flood hazards and projected impact on the built environment. Engineering analyses were performed for each studied flooding source to calculate its 1-percent-annual-chance flood elevations; elevations corresponding to other floods (e.g. 10-, 4-, 2-, 0.2-percent annual chance, etc.) may have also been computed for certain flooding sources. Engineering models and methods are described in detail in Section 5.0 of this FIS Report. The modeled elevations at cross sections were used to delineate the floodplain boundaries on the FIRM; between cross sections, the boundaries were interpolated using elevation data from various sources. More information on specific mapping methods is provided in Section 6.0 of this FIS Report.

Depending on the accuracy of available topographic data (Table 22), study methodologies employed (Section 5.0), and flood risk, certain flooding sources may be mapped to show both the 1-percent and 0.2-percent-annual-chance floodplain boundaries, regulatory water surface elevations (BFEs), and/or a regulatory floodway. Similarly, other flooding sources may be mapped to show only the 1-percent-annual-chance floodplain boundary on the FIRM, without published water surface elevations. In cases where the 1-percent and 0.2-percent-annual-chance floodplain boundaries are close together, only the 1-percent-annual-chance floodplain boundary is shown on the FIRM. Figure 3, "Map Legend for FIRM", describes the flood zones that are used on the FIRMs to account for the varying levels of flood risk that exist along flooding sources within the project area. Table 2 and Table 3 indicate the flood zone designations for each flooding source and each community within Wheatland County, respectively.

Table 2, "Flooding Sources Included in this FIS Report," lists each flooding source, including its study limits, affected communities, mapped zone on the FIRM, and the completion date of its engineering analysis from which the flood elevations on the FIRM and in the FIS Report were derived. Descriptions and dates for the latest hydrologic and hydraulic analyses of the flooding sources are shown in Table 12. Floodplain boundaries for these flooding sources are shown on the FIRM (published separately) using the symbology described in Figure 3. On the map, the 1-percent-annual-chance floodplain corresponds to the SFHAs. The 0.2-percent-annual-chance floodplain shows areas that, although out of the regulatory floodplain, are still subject to flood hazards.

Small areas within the floodplain boundaries may lie above the flood elevations but cannot be shown due to limitations of the map scale and/or lack of detailed topographic data. The procedures to remove these areas from the SFHA are described in Section 6.5 of this FIS Report.

Table 2: Flooding Sources Included in this FIS Report

Flooding Source	Community	Downstream Limit	Upstream Limit	HUC-8 Sub- Basin(s)	Length (mi) (streams or coastlines)	Floodway (Y/N)	Zone shown on FIRM	Date of Analysis
American Fork	Wheatland County Unincorporated Areas	Confluence with the Musselshell River near Harlowton, MT	Approximately 3.5 stream miles upstream	10040201	3.5	N	А	1981
Antelope Creek	Wheatland County Unincorporated Areas	Confluence with the Musselshell River near Harlowton, MT	Upstream of US Highway 12	10040201	1.1	Υ	AE, AO	2020
Antelope Creek	Wheatland County Unincorporated Areas	Upstream of US Highway 12	Approximately 2.9 stream mles upstream of US Highway 12	10040201	2.9	N	AE	2016
Antelope Overflow	Harlowton, City of; Wheatland County Unincorporated Areas	Confluence with Antelope Creek near Harlowton, MT	Point of diversion from Antelope Creek near Harlowton, MT	10040201	0.8	Y	AE	2020
Harlowton Overflow Channel	Harlowton, City of; Wheatland County Unincorporated Areas		Point of diversion from the Musselshell River west of Harlowton, MT	10040201	2.9	N	AE	2016
Musselshell River	Wheatland County Unincorporated Areas		Approximately 0.6 stream mles downstream of Red Bridge Road	10040201	36.9	N	AE	2016
Musselshell River	Wheatland County Unincorporated Areas	mles downstream of Red	Approximately 5.1 stream mles upstream of US Highway 191	10040201	8.4	Υ	AE	2016
Musselshell River and Zone A Tributaries	Wheatland County Unincorporated Areas	See FIRMs	See FIRMs	10040201	75.0	N	А	1981
Railroad Split	Wheatland County Unincorporated Areas	Red Bridge Road near Harlowton, MT	Point of diversion from Antelope Creek near Harlowton, MT	10040201	0.7	Y	AE	2016
Roberts Creek	Wheatland County Unincorporated Areas	See FIRMs	See FIRMs	10040201	3.5	N	А	1981

#### 2.2 Floodways

Encroachment on floodplains, such as structures and fill, reduces flood-carrying capacity, increases flood heights and velocities, and increases flood hazards in areas beyond the encroachment itself. One aspect of floodplain management involves balancing the economic gain from floodplain development against the resulting increase in flood hazard.

For purposes of the NFIP, a floodway is used as a tool to assist local communities in balancing floodplain development against increasing flood hazard. With this approach, the area of the 1-percent-annual-chance floodplain on a river is divided into a floodway and a floodway fringe based on hydraulic modeling. The floodway is the channel of a stream, plus any adjacent floodplain areas, that must be kept free of encroachment in order to carry the 1-percent-annual-chance flood. The floodway fringe is the area between the floodway and the 1-percent-annual-chance floodplain boundaries where encroachment is permitted. The floodway must be wide enough so that the floodway fringe could be completely obstructed without increasing the water surface elevation of the 1-percent-annual-chance flood more than 1 foot at any point. Typical relationships between the floodway and the floodway fringe and their significance to floodplain development are shown in Figure 4.

To participate in the NFIP, Federal regulations require communities to limit increases caused by encroachment to 1.0 foot, provided that hazardous velocities are not produced. Regulations for Montana require communities in Wheatland County to limit increases caused by encroachment to 0.5 foot and several communities have adopted additional restrictions. The floodways in this project are presented to local agencies as minimum standards that can be adopted directly or that can be used as a basis for additional floodway projects.




Figure 4: Floodway Schematic

Floodway widths presented in this FIS Report and on the FIRM were computed at cross sections. Between cross sections, the floodway boundaries were interpolated. For certain stream segments, floodways were adjusted so that the amount of floodwaters conveyed on each side of the floodplain would be reduced equally. The results of the floodway computations have been tabulated for selected cross sections and are shown in Table 23, "Floodway Data."

All floodways that were developed for this Flood Risk Project are shown on the FIRM using the symbology described in Figure 3. In cases where the floodway and 1-percent-annual-chance floodplain boundaries are either close together or collinear, only the floodway boundary has been shown on the FIRM. For information about the delineation of floodways on the FIRM, refer to Section 6.3.

#### 2.3 Base Flood Elevations

The hydraulic characteristics of flooding sources were analyzed to provide estimates of the elevations of floods of the selected recurrence intervals. The BFE is the elevation of the 1-percent-annual-chance flood. These BFEs are most commonly rounded to the whole foot, as shown on the FIRM, but in certain circumstances or locations they may be rounded to 0.1 foot. Cross section lines shown on the FIRM may also be labeled with the BFE rounded to 0.1 foot. Whole-foot BFEs derived from engineering analyses that apply to coastal areas, areas of ponding, or other static areas with little elevation change may also be shown at selected intervals on the FIRM.

BFEs are primarily intended for flood insurance rating purposes. Cross sections with BFEs shown on the FIRM correspond to the cross sections shown in the Floodway Data table and Flood Profiles in this FIS Report. For construction and/or floodplain management purposes, users are cautioned to use the flood elevation data presented in this FIS Report in conjunction with the data shown on the FIRM. For example, the user may use the FIRM to determine the stream station of a location of interest and then use the profile to determine the 1-percent annual chance elevation at that location. Because only selected cross sections may be shown on the FIRM for riverine areas, the profile should be used to obtain the flood elevation between mapped cross sections. Additionally, for riverine areas, whole-foot elevations shown on the FIRM may not exactly reflect the elevations derived from the hydraulic analyses; therefore, elevations obtained from the profile may more accurately reflect the results of the hydraulic analysis.

#### 2.4 Non-Encroachment Zones

This section is not applicable to this Flood Risk Project.

#### 2.5 Coastal Flood Hazard Areas

This section is not applicable to this Flood Risk Project.

#### 2.5.1 Water Elevations and the Effects of Waves

This section is not applicable to this Flood Risk Project.

# Figure 5: Wave Runup Transect Schematic

[Not Applicable to this Flood Risk Project]

#### 2.5.2 Floodplain Boundaries and BFEs for Coastal Areas

This section is not applicable to this Flood Risk Project.

#### 2.5.3 Coastal High Hazard Areas

This section is not applicable to this Flood Risk Project.

#### Figure 6: Coastal Transect Schematic

[Not Applicable to this Flood Risk Project]

#### 2.5.4 Limit of Moderate Wave Action

This section is not applicable to this Flood Risk Project.

#### **SECTION 3.0 – INSURANCE APPLICATIONS**

#### 3.1 National Flood Insurance Program Insurance Zones

For flood insurance applications, the FIRM designates flood insurance rate zones as described in Figure 3, "Map Legend for FIRM." Flood insurance zone designations are assigned to flooding sources based on the results of the hydraulic or coastal analyses. Insurance agents use the zones shown on the FIRM and depths and base flood elevations in this FIS Report in conjunction with information on structures and their contents to assign premium rates for flood insurance policies.

The 1-percent-annual-chance floodplain boundary corresponds to the boundary of the areas of special flood hazards (e.g. Zones A, AE, V, VE, etc.), and the 0.2-percent-annual-chance floodplain boundary corresponds to the boundary of areas of additional flood hazards.

Table 3 lists the flood insurance zones in Wheatland County.

**Table 3: Flood Zone Designations by Community** 

Community	Flood Zone(s)
Harlowton, City of	AE, X
Judith Gap, Town of*	D, X
Wheatland County Unincorporated Areas	A, AE, AO, D, X

^{*} No Special Flood Hazard Areas Identified

#### **SECTION 4.0 – AREA STUDIED**

#### 4.1 Basin Description

Table 4 contains a description of the characteristics of the HUC-8 sub-basins within which each community falls. The table includes the main flooding sources within each basin, a brief description of the basin, and its drainage area.

**Table 4: Basin Characteristics** 

HUC-8 Sub-Basin Name	HUC-8 Sub-Basin Number	Primary Flooding Source	Description of Affected Area	Drainage Area (square miles)
Judith	10040103	Musselshell River	Affecting a very small portion of northern Wheatland County near the Town of Judith Gap	2,762
Upper Musselshell	10040201	Musselshell River	Originates at the confluence of the North Fork and South Fork of the Musselshell River near the Town of Martinsdale, Montana to the confluence with the Missouri River and Fort Peck Reservoir	4,011

#### 4.2 Principal Flood Problems

Table 5 contains a description of the principal flood problems that have been noted for Wheatland County by flooding source.

**Table 5: Principal Flood Problems** 

Flooding Source	Description of Flood Problems
Antelope Creek	Historic flooding has been related to runoff from intense rainfall events. The flood of record occurred in 1950 as a result of an intense rain storm. A peak discharge of 24,400 cfs was recorded by indirect methods after the flood which occurred on June 17, 1950. USGS gage 06120900 was installed in 1955 at approximately the same location as the indirect flow measurement.
Antelope Overflow	A storm on July 12, 1962, caused flooding in Harlowton from Antelope Overflow. This flood had a discharge of 749 cfs and was approximately equal to a 2-percent-annual-chance flood event.
Harlowton Overflow Channel	Flooding originates from two sources, direct rainfall and snowmelt runoff. This is the principal flooding source in the City of Harlowton. During flooding conditions, the channel flows easterly along the northern side of the Chicago, Milwaukee, St. Paul & Pacific Railroad. Floodwaters from Harlowton Overflow Channel join Jawbone Creek, pass through a bridge on the Lewistown Branch of the Chicago, Milwaukee, St. Paul & Pacific Railroad, and empty into Antelope Creek, east of Harlowton. Direct rainfall and snowmelt runoff from the local 3-square-mile watershed above the U.S. Highway 191 embankment contributes to flooding along Harlowton Overflow Channel and Jawbone Creek. This watershed produced a flood of 200 cfs in June 1979 (approximately a 10-percent-annual-chance event).
	Floodwaters from Musselshell River also contribute to flooding along Harlowton Overflow Channel. Some of the flooding from Musselshell River overflows the channel banks north of the railroad bridge west of Harlowton and flows easterly until it combines with Harlowton Overflow Channel west of U.S. Highway 191. Floods from the overflow of Musselshell River have occurred in June 1975 and 1967. The 1975 flood was approximately a 0.4-percent-annual-chance event and transferred 600 cfs to Harlowton Overflow Channel. These floods have caused substantial damage to St. Josephs Park and commercial and residential properties in the southern one-third of Harlowton.
Musselshell River	Most flooding is from spring snowmelt and runoff from intense rainfall events where the river overtops its banks. The maximum flood of record occurred on May 2011 as a result of rapid snowmelt. A peak discharge of 8,900 cubic feet per second (cfs) was recorded on May 26, 2011 at U.S. Geological Survey (USGS) gage 06123030 near Shawmut, Montana.

Table 6 contains information about historic flood elevations in the communities within Wheatland County.

# Table 6: Historic Flooding Elevations [Not Applicable to this Flood Risk Project]

#### 4.3 Non-Levee Flood Protection Measures

This section is not applicable to this Flood Risk Project.

# Table 7: Non-Levee Flood Protection Measures [Not Applicable to this Flood Risk Project]

#### 4.4 Levees

This section is not applicable to this Flood Risk Project.

Table 8: Levees

[Not Applicable to this Flood Risk Project]

#### **SECTION 5.0 – ENGINEERING METHODS**

For the flooding sources in the community, standard hydrologic and hydraulic study methods were used to determine the flood hazard data required for this study. Flood events of a magnitude that are expected to be equaled or exceeded at least once on the average during any 10-, 25-, 50-, 100-, or 500-year period (recurrence interval) have been selected as having special significance for floodplain management and for flood insurance rates. These events, commonly termed the 10-, 25-, 50-, 100-, and 500-year floods, have a 10-, 4-, 2-, 1-, and 0.2-percent-annual-chance, respectively, of being equaled or exceeded during any year.

Although the recurrence interval represents the long-term, average period between floods of a specific magnitude, rare floods could occur at short intervals or even within the same year. The risk of experiencing a rare flood increases when periods greater than 1 year are considered. For example, the risk of having a flood that equals or exceeds the 100-year flood (1-percent chance of annual exceedance) during the term of a 30-year mortgage is approximately 26 percent (about 3 in 10); for any 90-year period, the risk increases to approximately 60 percent (6 in 10). The analyses reported herein reflect flooding potentials based on conditions existing in the community at the time of completion of this study. Maps and flood elevations will be amended periodically to reflect future changes.

#### 5.1 Hydrologic Analyses

Hydrologic analyses were carried out to establish the peak elevation-frequency relationships for floods of the selected recurrence intervals for each flooding source studied. Hydrologic analyses are typically performed at the watershed level. Depending on factors such as watershed size and shape, land use and urbanization, and natural or man-made storage, various models or methodologies may be applied. A summary of the hydrologic methods applied to develop the discharges used in the hydraulic analyses for each stream is provided in Table 12. Greater detail (including assumptions, analysis, and results) is available in the archived project documentation.

A summary of the discharges is provided in Table 9. Stream gage information is provided in Table 11.

**Table 9: Summary of Discharges** 

			Drainage		Pe	eak Discharge	(cfs)	
Flooding Source	Location	River Station	Area (Square Miles)	10% Annual Chance	4% Annual Chance	2% Annual Chance	1% Annual Chance	0.2% Annual Chance
Antelope Creek	Alkali Creek	13306	91.2	1,520	4,920	10,640	21,490	91,550
Antelope Creek	Antelope Creek	20787	71.6	1,290	4,230	9,230	18,800	81,310
Musselshell River	USGS Station 06123030	25770	1,515	3,495	5,673	7,665	9,968	16,580
Musselshell River	River Mile 262	68803	1,495	3,449	5,568	7,500	9,729	16,110
Musselshell River	River Mile 268.7	103737	1,453	3,356	5,360	7,174	9,258	15,190
Musselshell River	American Fork	161024	1,231	2,863	4,290	5,533	6,925	10,770
Musselshell River	USGS Station 06120500	212531	1,118	2,610	3,768	4,756	5,848	8,816
Musselshell River	Milton Creek	228203	1,094	2,595	3,742	4,722	5,804	8,747
Musselshell River	Mud Creek	239663	981	2,522	3,617	4,552	5,586	8,407

Figure 7: Frequency Discharge-Drainage Area Curves
[Not Applicable to this Flood Risk Project]

Table 10: Summary of Non-Coastal Stillwater Elevations

[Not Applicable to this Flood Risk Project]

**Table 11: Stream Gage Information used to Determine Discharges** 

		Agency		Drainage	Period of	Record
Flooding Source	Gage Identifier	that Maintains Gage	Site Name	Area (Square Miles)	From	То
Antelope Creek	06120900	USGS	Antelope Creek at Harlowton, Montana	91	1950	1980
Musselshell River	06120500	USGS	Musselshell River at Harlowton MT	1,125	1909	2014
Musselshell River	06123030	USGS	Musselshell River above Mud Creek, near Shawmut	1,518	1998	2015

#### 5.2 Hydraulic Analyses

Analyses of the hydraulic characteristics of flooding from the sources studied were carried out to provide estimates of the elevations of floods of the selected recurrence intervals. Base flood elevations on the FIRM represent the elevations shown on the Flood Profiles and in the Floodway Data tables in the FIS Report. Rounded whole-foot elevations may be shown on the FIRM in coastal areas, areas of ponding, and other areas with static base flood elevations. These whole-foot elevations may not exactly reflect the elevations derived from the hydraulic analyses. Flood elevations shown on the FIRM are primarily intended for flood insurance rating purposes. For construction and/or floodplain management purposes, users are cautioned to use the flood elevation data presented in this FIS Report in conjunction with the data shown on the FIRM. The hydraulic analyses for this FIS were based on unobstructed flow. The flood elevations shown on the profiles are thus considered valid only if hydraulic structures remain unobstructed, operate properly, and do not fail.

For streams for which hydraulic analyses were based on cross sections, locations of selected cross sections are shown on the Flood Profiles (Exhibit 1). For stream segments for which a floodway was computed (Section 6.3), selected cross sections are also listed in Table 23, "Floodway Data."

A summary of the methods used in hydraulic analyses performed for this project is provided in Table 12. Roughness coefficients are provided in Table 13. Roughness coefficients are values representing the frictional resistance water experiences when passing overland or through a channel. They are used in the calculations to determine water surface elevations. Greater detail (including assumptions, analysis, and results) is available in the archived project documentation.

Table 12: Summary of Hydrologic and Hydraulic Analyses

Flooding Source	Study Limits Downstream Limit	Study Limits Upstream Limit	Hydrologic Model or Method Used	Hydraulic Model or Method Used	Date Analyses Completed	Flood Zone on FIRM	Special Considerations
American Fork	Confluence with the Musselshell River near Harlowton, MT	Approximately 3.5 stream miles upstream	Other	Other	11/01/1979	А	Aerial photographs of the 1975 Mussellshell River flood and USGS Quadrangle maps were used to determine the channel location and approximate limits of flooding
Antelope Creek	Confluence with the Musselshell River near Harlowton, MT	Upstream of US Highway 12	Expected Moments Algorithm	HEC-RAS, 4.1.0	07/17/2020	AE w/ Floodway, AO	
Antelope Creek	Upstream of US Highway 12	Approximately 2.9 stream mles upstream of US Highway 12	Expected Moments Algorithm	HEC-RAS, 4.1.0	06/15/2016	AE	
Antelope Overflow	Confluence with Antelope Creek near Harlowton, MT	Point of diversion from Antelope Creek near Harlowton, MT	Expected Moments Algorithm	HEC-RAS, 4.1.0	07/17/2020	AE w/ Floodway	
Harlowton Overflow Channel	Confluence with the Musselshell River near Harlowton, MT	Point of diversion from the Musselshell River west of Harlowton, MT	Two site logarithmic interpolation methods with USGS WRIR 03-4308	HEC-RAS, 4.1.0	06/15/2016	AE	
Musselshell River	Wheatland County Eastern Boundary	Approximately 0.6 stream mles downstream of Red Bridge Road	Two site logarithmic interpolation methods with USGS WRIR 03-4308	HEC-RAS, 4.1.0	06/15/2016	AE	

Table 12: Summary of Hydrologic and Hydraulic Analyses (continued)

Flooding Source	Study Limits Downstream Limit	Study Limits Upstream Limit	Hydrologic Model or Method Used	Hydraulic Model or Method Used	Date Analyses Completed	Flood Zone on FIRM	Special Considerations
Musselshell River	Approximately 0.6 stream mles downstream of Red Bridge Road	Approximately 5.1 stream mles upstream of US Highway 191	Two site logarithmic interpolation methods with USGS WRIR 03-4308	HEC-RAS, 4.1.0	06/15/2016	AE w/ Floodway	Aerial photographs of the 1975 Mussellshell River flood were used to determine the approximate flooding
Musselshell River and Zone A Tributaries	See FIRMs	See FIRMs	Other	Other	11/01/1979	А	
Railroad Split	Red Bridge Road near Harlowton, MT	Point of diversion from Antelope Creek near Harlowton, MT	Two site logarithmic interpolation methods with USGS WRIR 03-4308	HEC-RAS, 4.1.0	06/15/2016	AE w/ Floodway	
Roberts Creek	See FIRMs	See FIRMs	Other	Other	11/01/1979	А	Approximate limits of flooding were determined using Montana Department of Highways low-level aerial photographs of the channel

**Table 13: Roughness Coefficients** 

Flooding Source	Channel "n"	Overbank "n"
Antelope Creek	0.035-0.065	0.058-0.130
Antelope Overflow	0.044-0.075	0.060-0.100
Harlowton Overflow Channel	0.039-0.075	0.058-0.078
Musselshell River	0.035-0.090	0.058-0.200
Railroad Split	0.050-0.065	0.051-0.070

#### 5.3 Coastal Analyses

This section is not applicable to this Flood Risk Project.

**Table 14: Summary of Coastal Analyses** 

[Not Applicable to this Flood Risk Project]

#### 5.3.1 Total Stillwater Elevations

This section is not applicable to this Flood Risk Project.

Figure 8: 1% Annual Chance Total Stillwater Elevations for Coastal Areas

[Not Applicable to this Flood Risk Project]

**Table 15: Tide Gage Analysis Specifics** 

[Not Applicable to this Flood Risk Project]

#### 5.3.2 Waves

This section is not applicable to this Flood Risk Project.

#### 5.3.3 Coastal Erosion

This section is not applicable to this Flood Risk Project.

#### 5.3.4 Wave Hazard Analyses

This section is not applicable to this Flood Risk Project.

**Table 16: Coastal Transect Parameters** 

[Not Applicable to this Flood Risk Project]

**Figure 9: Transect Location Map** 

[Not applicable to this Flood Risk Project]

#### 5.4 Alluvial Fan Analyses

This section is not applicable to this Flood Risk Project.

Table 17: Summary of Alluvial Fan Analyses
[Not Applicable to this Flood Risk Project]

Table 18: Results of Alluvial Fan Analyses [Not Applicable to this Flood Risk Project]

#### **SECTION 6.0 – MAPPING METHODS**

#### 6.1 Vertical and Horizontal Control

All FIS Reports and FIRMs are referenced to a specific vertical datum. The vertical datum provides a starting point against which flood, ground, and structure elevations can be referenced and compared. Until recently, the standard vertical datum used for newly created or revised FIS Reports and FIRMs was the National Geodetic Vertical Datum of 1929 (NGVD29). With the completion of the North American Vertical Datum of 1988 (NAVD88), many FIS Reports and FIRMs are now prepared using NAVD88 as the referenced vertical datum.

Flood elevations shown in this FIS Report and on the FIRMs are referenced to NAVD88. These flood elevations must be compared to structure and ground elevations referenced to the same vertical datum. For information regarding conversion between NGVD29 and NAVD88 or other datum conversion, visit the National Geodetic Survey website at <a href="https://www.ngs.noaa.gov">www.ngs.noaa.gov</a>.

Temporary vertical monuments are often established during the preparation of a flood hazard analysis for the purpose of establishing local vertical control. Although these monuments are not shown on the FIRM, they may be found in the archived project documentation associated with the FIS Report and the FIRMs for this community. Interested individuals may contact FEMA to access these data.

To obtain current elevation, description, and/or location information for benchmarks in the area, please visit the NGS website at <a href="https://www.ngs.noaa.gov">www.ngs.noaa.gov</a>.

The datum conversion locations and values that were calculated for Wheatland County are provided in Table 19.

Table 19: Countywide Vertical Datum Conversion
[Not Applicable to this Flood Risk Project]

Table 20: Stream-Based Vertical Datum Conversion
[Not Applicable to this Flood Risk Project]

#### 6.2 Base Map

The FIRMs and FIS Report for this project have been produced in a digital format. The flood hazard information was converted to a Geographic Information System (GIS) format that meets FEMA's FIRM Database specifications and geographic information standards. This information is provided in a digital format so that it can be incorporated into a local GIS and be accessed more easily by the community. The FIRM Database includes most of the tabular information contained in the FIS Report in such a way that the data can be associated with pertinent spatial features. For example, the information contained in the Floodway Data table and Flood Profiles can be linked to the cross sections that are shown on the FIRMs. Additional information about the FIRM Database and its contents can be found in FEMA's *Guidelines and Standards for Flood Risk Analysis and Mapping*, <a href="https://www.fema.gov/media-library/resources-documents/collections/361">www.fema.gov/media-library/resources-documents/collections/361</a>.

Base map information shown on the FIRM was derived from the sources described in Table 21.

**Table 21: Base Map Sources** 

Data Type	Data Provider	Data Date	Data Scale	Data Description
USDA-FSA-APFO NAIP MrSID Mosaic	USDA/FSA - Aerial Photography Field Office	10/01/2013	1:12,000	Color orthoimagery was provided for the county
Montana Corporate Boundaries	Montana State Library	09/24/2015	N/A	Politcal boundaries
FIRM Panel Boundary	Michael Baker International	12/14/2015	1:24,000	FIRM Panels
Montana Transportation Framework	Montana State Library	08/19/2014	N/A	Transportation lines
PLSS Framework	Montana State Library	07/07/2015	1:24,000	PLSS data were digitized from USGS quadrangles
Montana Hydrography Framework	Montana State Library	03/19/2015	N/A	Water Lines and Polygons
Structure Inventory	Musselshell Watershed Coalition	12/14/2015	N/A	General Structures

#### 6.3 Floodplain and Floodway Delineation

The FIRM shows tints, screens, and symbols to indicate floodplains and floodways as well as the locations of selected cross sections used in the hydraulic analyses and floodway computations.

For riverine flooding sources, the mapped floodplain boundaries shown on the FIRM have been delineated using the flood elevations determined at each cross section;

between cross sections, the boundaries were interpolated using the topographic elevation data described in Table 22.

In cases where the 1-percent and 0.2-percent-annual-chance floodplain boundaries are close together, only the 1-percent-annual-chance floodplain boundary has been shown. Small areas within the floodplain boundaries may lie above the flood elevations but cannot be shown due to limitations of the map scale and/or lack of detailed topographic data.

The floodway widths presented in this FIS Report and on the FIRM were computed for certain stream segments on the basis of equal conveyance reduction from each side of the floodplain. Floodway widths were computed at cross sections. Between cross sections, the floodway boundaries were interpolated. Table 2 indicates the flooding sources for which floodways have been determined. The results of the floodway computations for those flooding sources have been tabulated for selected cross sections and are shown in Table 23, "Floodway Data."

Table 22: Summary of Topographic Elevation Data used in Mapping

		Source for Top	ographic Elevati	on Data	
Community	Flooding Source	Description	Vertical Accuracy	Horizontal Accuracy	Citation
Wheatland County	Musselshell River & Antelope Creek	LiDAR	1 meter GSD	1 meter	Quantum Spatial, 2016
Wheatland County	Musselshell River	LiDAR	1 meter GSD	3 foot	NRCS/ USACE 2012
Wheatland County	Musselshell River Zone A	Aerial Photographs & USGS Quadrangles			Montana Department of Highways, 1976, USGS, 1975
Wheatland County	Roberts Creek Zone A	Aerial Photographs	N/A	1:7,200	Montana Department of Highways, 1976

BFEs shown at cross sections on the FIRM represent the 1-percent-annual-chance water surface elevations shown on the Flood Profiles and in the Floodway Data tables in the FIS Report.

In Montana, the designated floodway is developed using a 0.5 foot surcharge instead of the Federal maximum of 1.0 foot (MDNCR 2014). These criteria take precedence over the minimum Federal criteria for purposes of regulating development in the floodplain, as set forth in the Code of Federal Regulations, 24 CFR, 1910 (d). The floodways computed for this study are based on a maximum increase of 0.5 foot.

**Table 23: Floodway Data** 

FLOODING SOURCE			FLOODWAY			BASE FLOOD WATER SURFACE ELEVATION (FEET NAVD 88)			
CROSS SECTION	DISTANCE ¹	WIDTH (FEET)	SECTION AREA (SQUARE FEET)	MEAN VELOCITY (FEET PER SECOND)	REGULATORY	WITHOUT	WITH FLOODWAY	INCREASE	
Antelope Creek			,	•					
A B C D	415 1,753 3,223 5,001	1,499 1,820 530 370	4,174 3,089 3,458 3,473	3.8 6.3 5.5 6.0	4,151.7 4,162.0 4,177.7 4,185.4	4,151.7 4,162.0 4,177.7 4,185.4	4,152.0 4,162.1 4,177.8 4,185.8	0.3 0.1 0.1 0.4	
¹ Feet above confluence	with Musselshell Rive	er							
	FEDERAL EMERGENCY MANAGEMENT AGENCY WHEATLAND COUNTY, MT			FL	OODWAY	DATA			
AND II	ID INCORPORATED AREAS			FLOODING SOURCE: ANTELOPE CREEK					

FLOODING SOURCE FLOODWAY WATER SURFACE ELEVATION (FEET NAVD 88)		CE ELEVATION						
CROSS SECTION	DISTANCE ¹	WIDTH (FEET)	SECTION AREA (SQUARE FEET)	MEAN VELOCITY (FEET PER SECOND)	REGULATORY	WITHOUT FLOODWAY	WITH FLOODWAY	INCREASE
Antelope Overflow			. ==.,	020027				
A B C D	263 1,997 2,842 4,201	920 405 585 115	2,693 1,162 371 332	3.6 2.2 6.7 3.2	4,159.4 4,162.0 4,165.2 4,184.2	4,159.4 4,162.0 4,165.2 4,184.2	4,159.6 4,162.4 4,165.3 4,184.3	0.2 0.4 0.1 0.1
	MERGENCY MA				FL	OODWAY	DATA	

FLOODING SOURCE: ANTELOPE OVERFLOW

**AND INCORPORATED AREAS** 

23

FLOODING SOURCE		FLOODWAY			BASE FLOOD WATER SURFACE ELEVATION (FEET NAVD 88)			
CROSS SECTION	DISTANCE ¹	WIDTH (FEET)	SECTION AREA (SQUARE FEET)	MEAN VELOCITY (FEET PER SECOND)	REGULATORY	WITHOUT FLOODWAY	WITH FLOODWAY	INCREAS
Musselshell River								
DO.	405.000	4 204	0.000	2.0	4.400.0	4.400.0	4 400 0	0.0
BQ BR	195,296	1,321	2,000	2.9	4,128.8	4,128.8	4,129.0	0.2
	195,945	567	1,196	4.9	4,130.6	4,130.6	4,131.1	0.5
BS	197,464	207	1,128	5.2	4,138.2	4,138.2	4,138.2	0.0
BT	199,201	198	915	6.4	4,140.9	4,140.9	4,141.1	0.2
BU	200,520	175	950	6.2	4,145.3	4,145.3	4,145.6	0.3
BV	201,577	450	1,875	3.1	4,147.6	4,147.6	4,148.0	0.4
BW	203,019	420	1,397	4.2	4,150.9	4,150.9	4,151.3	0.4
BX	205,924	1,513	3,165	1.9	4,155.2	4,155.2	4,155.7	0.5
BY	207,579	777	1,715	3.4	4,159.5	4,159.5	4,160.0	0.5
BZ	209,174	911	2,019	2.9	4,164.5	4,164.5	4,164.7	0.2
CA	211,011	944	2,587	2.2	4,168.8	4,168.8	4,169.1	0.3
СВ	212,036	826	1,583	3.5	4,172.1	4,172.1	4,172.6	0.5
CC	213,701	293	1,008	5.5	4,178.8	4,178.8	4,178.8	0.0
CD	215,293	898	1,352	4.1	4,182.4	4,182.4	4,182.6	0.2
CE	216,374	687	2,150	2.6	4,185.5	4,185.5	4,185.9	0.4
CF	217,518	1,148	1,702	3.3	4,187.9	4,187.9	4,188.2	0.3
CG	219,064	280	1,102	5.0	4,192.4	4,192.4	4,192.9	0.5
CH	220,617	381	1,313	4.2	4,195.4	4,195.4	4,195.9	0.5
CI	222,113	634	1,823	3.0	4,199.4	4,199.4	4,199.9	0.5
CJ	223,428	411	1,316	4.2	4,204.2	4,204.2	4,204.7	0.5
CK	224,628	543	1,521	3.6	4,205.4	4,205.4	4,205.8	0.4
CL	225,751	404	1,308	4.2	4,209.5	4,209.5	4,210.0	0.5
CM	227,632	906	2,970	2.0	4,215.2	4,215.2	4,215.4	0.2
CN	229,039	245	1,010	5.5	4,220.4	4,220.4	4,220.4	0.0
CO	230,408	195	780	7.2	4,223.7	4,223.7	4,224.0	0.3
CP	231,434	378	1,243	4.5	4,226.9	4,226.9	4,227.3	0.4

¹Feet above eastern county line

TABLE 23

# WHEATLAND COUNTY, MT AND INCORPORATED AREAS

#### **FLOODWAY DATA**

FLOODING SOURCE: MUSSELSHELL RIVER

FLOODING S	OURCE		FLOODWAY		BASE FLOOD WATER SURFACE ELEVATION (FEET NAVD 88)			
CROSS SECTION	DISTANCE ¹	WIDTH (FEET)	SECTION AREA (SQUARE FEET)	MEAN VELOCITY (FEET PER SECOND)	REGULATORY	WITHOUT FLOODWAY	WITH FLOODWAY	INCREAS
Musselshell River (Cont'd)			1221)	<u> </u>				
CQ CR CS CT CU	232,654 234,119 235,738 237,313 238,761	220 413 780 776 1,187	1,076 1,436 3,028 1,763 2,276	5.2 3.9 1.8 3.2 2.5	4,230.2 4,233.7 4,236.5 4,239.3 4,242.3	4,230.2 4,233.7 4,236.5 4,239.3 4,242.3	4,230.6 4,234.2 4,237.0 4,239.8 4,242.4	0.4 0.5 0.5 0.5 0.1
	y line  MERGENCY MA				FL	.OODWAY	DATA	

FLOODING SOURCE: MUSSELSHELL RIVER

**AND INCORPORATED AREAS** 

23

FLOODING S	OURCE		FLOODWAY		BASE FLOOD WATER SURFACE ELEVATION (FEET NAVD 88)			
CROSS SECTION	DISTANCE ¹	WIDTH (FEET)	SECTION AREA (SQUARE FEET)	MEAN VELOCITY (FEET PER SECOND)	REGULATORY	WITHOUT FLOODWAY	WITH FLOODWAY	INCREASE
Railroad Split				0210112				
A B C	0 1,982 3,506	241 985 314	197 3,258 1,173	5.0 1.6 4.9	4,136.70 4,143.9 4,153.6	4,136.70 4,143.9 4,153.6	4,137.10 4,144.4 4,153.9	0.4 0.5 0.3
	MERGENCY MA				FL	OODWAY	DATA	

# Table 24: Flood Hazard and Non-Encroachment Data for Selected Streams [Not Applicable to this Flood Risk Project]

#### 6.4 Coastal Flood Hazard Mapping

This section is not applicable to this Flood Risk Project.

# Table 25: Summary of Coastal Transect Mapping Considerations [Not Applicable to this Flood Risk Project]

#### 6.5 FIRM Revisions

This FIS Report and the FIRM are based on the most up-to-date information available to FEMA at the time of its publication; however, flood hazard conditions change over time. Communities or private parties may request flood map revisions at any time. Certain types of requests require submission of supporting data. FEMA may also initiate a revision. Revisions may take several forms, including Letters of Map Amendment (LOMAs), Letters of Map Revision Based on Fill (LOMR-Fs), Letters of Map Revision (LOMRs) (referred to collectively as Letters of Map Change (LOMCs)), Physical Map Revisions (PMRs), and FEMA-contracted restudies. These types of revisions are further described below. Some of these types of revisions do not result in the republishing of the FIS Report. To assure that any user is aware of all revisions, it is advisable to contact the community repository of flood-hazard data (shown in Table 30, "Map Repositories").

#### 6.5.1 Letters of Map Amendment

A LOMA is an official revision by letter to an effective NFIP map. A LOMA results from an administrative process that involves the review of scientific or technical data submitted by the owner or lessee of property who believes the property has incorrectly been included in a designated SFHA. A LOMA amends the currently effective FEMA map and establishes that a specific property is not located in a SFHA.

To obtain an application for a LOMA, visit <a href="www.fema.gov/letter-map-amendment-loma">www.fema.gov/letter-map-amendment-loma</a> and download the form "MT-1 Application Forms and Instructions for Conditional and Final Letters of Map Amendment and Letters of Map Revision Based on Fill". Visit the "Flood Map-Related Fees" section to determine the cost, if any, of applying for a LOMA.

FEMA offers a tutorial on how to apply for a LOMA. The LOMA Tutorial Series can be accessed at <a href="https://www.fema.gov/online-tutorials">www.fema.gov/online-tutorials</a>.

For more information about how to apply for a LOMA, call the FEMA Mapping and Insurance eXchange; toll free, at 1-877-FEMA MAP (1-877-336-2627).

#### 6.5.2 Letters of Map Revision Based on Fill

A LOMR-F is an official revision by letter to an effective NFIP map. A LOMR-F states FEMA's determination concerning whether a structure or parcel has been elevated on fill above the base flood elevation and is, therefore, excluded from the SFHA.

Information about obtaining an application for a LOMR-F can be obtained in the same manner as that for a LOMA, by visiting <a href="www.fema.gov/letter-map-amendment-loma">www.fema.gov/letter-map-amendment-loma</a> for the "MT-1 Application Forms and Instructions for Conditional and Final Letters of Map Amendment and Letters of Map Revision Based on Fill" or by calling the FEMA Mapping and Insurance eXchange, toll free, at 1-877-FEMA MAP (1-877-336-2627). Fees for applying for a LOMR-F, if any, are listed in the "Flood Map-Related Fees" section.

A tutorial for LOMR-F is available at www.fema.gov/online-tutorials.

#### 6.5.3 Letters of Map Revision

A LOMR is an official revision to the currently effective FEMA map. It is used to change flood zones, floodplain and floodway delineations, flood elevations and planimetric features. All requests for LOMRs should be made to FEMA through the chief executive officer of the community, since it is the community that must adopt any changes and revisions to the map. If the request for a LOMR is not submitted through the chief executive officer of the community, evidence must be submitted that the community has been notified of the request.

To obtain an application for a LOMR, visit <a href="www.fema.gov/media-library/assets/documents/1343">www.fema.gov/media-library/assets/documents/1343</a> and download the form "MT-2 Application Forms and Instructions for Conditional Letters of Map Revision and Letters of Map Revision". Visit the "Flood Map-Related Fees" section to determine the cost of applying for a LOMR. For more information about how to apply for a LOMR, call the FEMA Mapping and Insurance eXchange; toll free, at 1-877-FEMA MAP (1-877-336-2627) to speak to a Map Specialist.

Previously issued mappable LOMCs (including LOMRs) that have been incorporated into the Wheatland County FIRM are listed in Table 26.

## **Table 26: Incorporated Letters of Map Change**

#### [Not Applicable to this Flood Risk Project]

#### 6.5.4 Physical Map Revisions

A Physical Map Revisions (PMR) is an official republication of a community's NFIP map to effect changes to base flood elevations, floodplain boundary delineations, regulatory floodways and planimetric features. These changes typically occur as a result of structural works or improvements, annexations resulting in additional flood hazard areas or correction to base flood elevations or SFHAs.

The community's chief executive officer must submit scientific and technical data to FEMA to support the request for a PMR. The data will be analyzed and the map will be revised if warranted. The community is provided with copies of the revised information and is afforded a review period. When the base flood elevations are changed, a 90-day appeal period is provided. A 6-month adoption period for formal approval of the revised map(s) is also provided.

For more information about the PMR process, please visit <u>www.fema.gov</u> and visit the "Flood Map Revision Processes" section.

#### 6.5.5 Contracted Restudies

The NFIP provides for a periodic review and restudy of flood hazards within a given community. FEMA accomplishes this through a national watershed-based mapping needs assessment strategy, known as the Coordinated Needs Management Strategy (CNMS). The CNMS is used by FEMA to assign priorities and allocate funding for new flood hazard analyses used to update the FIS Report and FIRM. The goal of CNMS is to define the validity of the engineering study data within a mapped inventory. The CNMS is used to track the assessment process, document engineering gaps and their resolution, and aid in prioritization for using flood risk as a key factor for areas identified for flood map updates. Visit <a href="www.fema.gov">www.fema.gov</a> to learn more about the CNMS or contact the FEMA Regional Office listed in Section 8 of this FIS Report.

#### 6.5.6 Community Map History

The current FIRM presents flooding information for the entire geographic area of Wheatland County. Previously, separate FIRMs, Flood Hazard Boundary Maps (FHBMs) and/or Flood Boundary and Floodway Maps (FBFMs) may have been prepared for the incorporated communities and the unincorporated areas in the county that had identified SFHAs. Current and historical data relating to the maps prepared for the project area are presented in Table 27, "Community Map History." A description of each of the column headings and the source of the date is also listed below.

- Community Name includes communities falling within the geographic area shown
  on the FIRM, including those that fall on the boundary line, nonparticipating
  communities, and communities with maps that have been rescinded.
  Communities with No Special Flood Hazards are indicated by a footnote. If all
  maps (FHBM, FBFM, and FIRM) were rescinded for a community, it is not listed
  in this table unless SFHAs have been identified in this community.
- Initial Identification Date (First NFIP Map Published) is the date of the first NFIP map that identified flood hazards in the community. If the FHBM has been converted to a FIRM, the initial FHBM date is shown. If the community has never been mapped, the upcoming effective date or "pending" (for Preliminary FIS Reports) is shown. If the community is listed in Table 27 but not identified on the map, the community is treated as if it were unmapped.
- Initial FHBM Effective Date is the effective date of the first FHBM. This date may be the same date as the Initial NFIP Map Date.
- FHBM Revision Date(s) is the date(s) that the FHBM was revised, if applicable.
- Initial FIRM Effective Date is the date of the first effective FIRM for the community.
- FIRM Revision Date(s) is the date(s) the FIRM was revised, if applicable. This is
  the revised date that is shown on the FIRM panel, if applicable. As countywide
  studies are completed or revised, each community listed should have its FIRM
  dates updated accordingly to reflect the date of the countywide study. Once the
  FIRMs exist in countywide format, as PMRs of FIRM panels within the county are
  completed, the FIRM Revision Dates in the table for each community affected by

the PMR are updated with the date of the PMR, even if the PMR did not revise all the panels within that community.

The initial effective date for the Wheatland County FIRMs in countywide format was [TBD].

**Table 27: Community Map History** 

Community Name	Initial Identification Date	Initial FHBM Effective Date	FHBM Revision Date(s)	Initial FIRM Effective Date	FIRM Revision Date(s)
Harlowton, City of	9/16/1981	N/A	N/A	9/16/1981	[TBD]
Judith Gap, Town of ^{1, 2}	N/A	N/A	N/A	[TBD]	N/A
Wheatland County Unincorporated Areas	11/6/1979	11/6/1979	N/A	9/16/1981	[TBD]

¹ No Special Flood Hazard Areas Identified

#### SECTION 7.0 - CONTRACTED STUDIES AND COMMUNITY COORDINATION

#### 7.1 Contracted Studies

Table 28 provides a summary of the contracted studies, by flooding source, that are included in this FIS Report.

Table 28: Summary of Contracted Studies Included in this FIS Report

Flooding Source	FIS Report Dated	Contractor	Number	Work Completed Date	Affected Communities
Antelope Creek	[TBD]	Morrison- Maierle, Inc.	HSFE06-12- J-0001	May 2016	Wheatland County Unincorporated Areas
American Fork	03/19/1981	Morrison- Maierle, Inc.	H-4747	November 1981	Wheatland County Unincorporated Areas
Antelope Creek	[TBD]	Morrison- Maierle, Inc.	HSFE06-12- J-0001	July 2020	Wheatland County Unincorporated Areas
Antelope Creek	[TBD]	Morrison- Maierle, Inc.	HSFE06-12- J-0001	May 2016	Wheatland County Unincorporated Areas
Antelope Overflow	[TBD]	Morrison- Maierle, Inc.	HSFE06-12- J-0001	May 2016	Harlowton, City of; Wheatland County Unincorporated Areas

² This community did not have a FIRM prior to the first countywide FIRM for Wheatland County

Table 28: Summary of Contracted Studies Included in this FIS Report (continued)

Flooding Source	FIS Report Dated	Contractor	Number	Work Completed Date	Affected Communities
Harlowton Overflow Channel	[TBD]	Morrison- Maierle, Inc.	HSFE06-12- J-0001	May 2016	Harlowton, City of; Wheatland County Unincorporated Areas
Musselshell River	[TBD]	Morrison- Maierle, Inc.	HSFE06-12- J-0001	May 2016	Wheatland County Unincorporated Areas
Musselshell River	[TBD]	Morrison- Maierle, Inc.	HSFE06-12- J-0001	May 2016	Wheatland County Unincorporated Areas
Musselshell River and Zone A Tributaries	03/19/1981	Morrison- Maierle, Inc.	H-4747	November 1981	Wheatland County Unincorporated Areas
Railroad Split	[TBD]	Morrison- Maierle, Inc.	HSFE06-12- J-0001	May 2016	Wheatland County Unincorporated Areas
Roberts Creek	03/19/1981	Morrison- Maierle, Inc.	H-4747	November 1981	Wheatland County Unincorporated Areas

#### 7.2 Community Meetings

The dates of the community meetings held for this Flood Risk Project and previous Flood Risk Projects are shown in Table 29. These meetings may have previously been referred to by a variety of names (Community Coordination Officer (CCO), Scoping, Discovery, etc.), but all meetings represent opportunities for FEMA, community officials, study contractors, and other invited guests to discuss the planning for and results of the project.

**Table 29: Community Meetings** 

Community	FIS Report Dated	Date of Meeting	Meeting Type	Attended By
Harlowton, City of	[TBD]			FEMA, State Department of Natural Resources and Conservation, and the study contractor.
·		[TBD]	CCO Meeting	[TBD]
Judith Gap, Town of	[TBD]	N/A	N/A	N/A
Wheatland County	[TBD]	12/01/2016	Scoping	FEMA, State Department of Natural Resources and Conservation, and the study contractor.
Unincorporated Areas		[TBD]	CCO Meeting	[TBD]

#### **SECTION 8.0 – ADDITIONAL INFORMATION**

Information concerning the pertinent data used in the preparation of this FIS Report can be obtained by submitting an order with any required payment to the FEMA Engineering Library. For more information on this process, see www.fema.gov.

Table 30 is a list of the locations where FIRMs for Wheatland County can be viewed. Please note that the maps at these locations are for reference only and are not for distribution. Also, please note that only the maps for the community listed in the table are available at that particular repository. A user may need to visit another repository to view maps from an adjacent community.

Community Address State Zip Code Citv Harlowton City Hall Harlowton, City of Harlowton MT 59036 17 South Central Ave Judith Gap, Town of¹ N/A N/A N/A N/A Wheatland County Wheatland County Court Clerk Harlowton MT 59036 Unincorporated Areas

201 A Avenue NW

**Table 30: Map Repositories** 

The National Flood Hazard Layer (NFHL) dataset is a compilation of effective FIRM Databases and LOMCs. Together they create a GIS data layer for a State or Territory. The NFHL is updated as studies become effective and extracts are made available to the public monthly. NFHL data can be viewed or ordered from the website shown in Table 31.

Table 31 contains useful contact information regarding the FIS Report, the FIRM, and other relevant flood hazard and GIS data. In addition, information about the State NFIP Coordinator and GIS Coordinator is shown in this table. At the request of FEMA, each Governor has designated an agency of State or territorial government to coordinate that State's or territory's NFIP activities. These agencies often assist communities in developing and adopting necessary floodplain management measures. State GIS Coordinators are knowledgeable about the availability and location of State and local GIS data in their state.

**Table 31: Additional Information** 

FEMA and the NFIP							
FEMA and FEMA Engineering Library website	www.fema.gov/national-flood-insurance-program-flood-hazard-mapping/engineering-library						
NFIP website	www.fema.gov/national-flood-insurance-program						
NFHL Dataset	msc.fema.gov						

¹ No Special Flood Hazard Areas Identified

**Table 31: Additional Information (continued)** 

	1
FEMA Region VIII	Denver Federal Center Building 710, Box 25267 Denver, CO 80225-0267 (303) 235-4800
Other Federal Agencies	
USGS website	www.usgs.gov
Hydraulic Engineering Center website	www.hec.usace.army.mil
State Agencies and Organization	ons
State NFIP Coordinator	Traci Sears, CFM Department of Natural Resources and Conservation Montana Floodplain Management Program 1424 9th Avenue P.O. Box 201601 Helena, MT, 59620-1601 Phone: (406) 444-6654 tsears@mt.gov
Montana Water Operations Bureau Chief	Steve Story, PE, CFM Department of Natural Resources and Conservation Montana Floodplain Management Program 1424 9th Avenue P.O. Box 201601 Helena, MT, 59620-1601 Phone: (406) 444-6816 sestory@mt.gov
Wheatland County Floodplain Administrator	Page Dringman PO Box 1256 Big Timber, MT 59011 Phone: (406) 932-5470 sgplanning@itstriangle.com
Montana Floodplain Engineer	Douglas Brugger, EI Department of Natural Resources and Conservation 1625 Eleventh Ave. Helena, MT 59601 Phone: (406) 444-6664 douglas.brugger@mt.gov
State GIS Coordinator	Erin Fashoway Statewide GIS Coordinator Montana State Library 1515 East 6 th Avenue Helena, MT 59620 Phone: (406) 444-9013 <u>EFashoway@mt.gov</u>

### **SECTION 9.0 – BIBLIOGRAPHY AND REFERENCES**

Table 32 includes sources used in the preparation of and cited in this FIS Report as well as additional studies that have been conducted in the study area.

Table 32: Bibliography and References

Citation in this FIS	Publisher/ Issuer	Publication Title, "Article," Volume, Number, etc.	Author/Editor	Place of Publication	Publication Date/ Date of Issuance	Link
Applied Geomorphol ogy and RATT, 2012	Applied Geomorphology and RATT	Musselshell River Flood Rehabilitation River Assessment Triage Team (RATT) Summary Report	Applied Geomorphol ogy and RATT	Bozeman, MT	2012	http://www.appliedgeom orph.com/
CivilGEO, 2016	CivilGEO Engineering Software	GeoHECRAS	CivilGEO	N/A	2016	http://www.civilgeo.com/
DNRC, 2014	Montana Department of Natural Resources and Conservation	2014 Model Regulations	DNRC	Helena, MT	2014	http://dnrc.mt.gov/divisio ns/water/operations/flood plain-management
Esri, 2012	Esri	ArcGIS Desktop: Release 10.1.	N/A	Redlands, CA	2012	http://www.esri.com/
FEMA, 2003	Federal Emergency Management Agency	Guidelines and Specifications for Hazard Mapping Partners, Appendix J.2.2:	N/A	N/A	2003	http://www.fema.gov/me dia-library- data/31d736ea5b9afbfd2 8a256538c4727ea/Appe ndix+J
FEMA, 2009	Federal Emergency Management Agency	Guidelines and Specifications for Hazard Mapping Partners, Appendix C:	N/A	N/A	2009	http://www.fema.gov/me dia- library/assets/documents /13948
FEMA, 2011	Federal Emergency Management Agency	cHECk-RAS, Version 2.0.1	N/A	N/A	2011	http://www.floodmaps.fe ma.gov/fhm/checkras/ch eck-ras.asp

Table 32: Bibliography and References (continued)

Citation in this FIS	Publisher/ Issuer	Publication Title, "Article," Volume, Number, etc.	Author/Editor	Place of Publication	Publication Date/ Date of Issuance	Link
FEMA, 2013	Federal Emergency Management Agency	RASPLOT, Version 3.0 beta	FEMA	N/A	2013	https://www.fema.gov/ra splot-version-30
FEMA, 2015	Federal Emergency Management Agency	Montana DNRC Cooperating Technical Partners Mapping Activity Statement (MAS): No. 2015-02, for Musselshell Watershed Project, Phase II	FEMA	N/A	2015	http://www.fema.gov/media-library/assets/documents/34953
MMI, 2016	Morrison-Maierle, Inc.	Survey Report, Musselshell River	ММІ	Helena, MT	2016	http://m-m.net/
Montana Department of Highways, 1976	State of Montana, Department of Highways	Aerial Photographs, Roll 302, Photos 123-133, Scale 1:7,200	State of Montana, Department of Highways	Helena, MT	1976	
Montana Department of Highways, 1975	State of Montana, Department of Highways	Aerial Photographs, Roll 278, Photos 202-203, Scale 1:7,200	State of Montana, Department of Highways	Helena, MT	1975	
NRCS, 2012	Natural Resources and Conservation Service	Light Detection and Ranging (LiDAR) Survey	NRCS	Bozeman, MT	2012	http://www.nrcs.usda.gov /wps/portal/nrcs/site/mt/h ome/
Parrett and Johnson, 2004	United States Geologic Survey	Methods for estimating flood frequency in Montana based on data through water year 1998.	USGS	Reston,VA	2004	http://wy- mt.water.usgs.gov/flood freq/index.htm

Table 32: Bibliography and References (continued)

Citation in this FIS	Publisher/ Issuer	Publication Title, "Article," Volume, Number, etc.	Author/Editor	Place of Publication	Publication Date/ Date of Issuance	Link
Pioneer, 2015	Pioneer Technical Services, Inc.	Musselshell River Floodplain Study -Phase 1, Final Field Reconnaissance and Hydraulic Structure Assessment Report.	Pioneer Technical Services, Inc.	Bozeman, MT	2015	http://pioneer- technical.com/
USACE, 2010	United States Army Corps of Engineers	HEC-RAS 4.1.0, Hydraulic Modeling Software.	USACE Hydrologic Engineering Center	Davis,CA	2010	http://www.hec.usace.ar my.mil/software/hec-ras/
Quantum Spatial, 2016	Quantum Spatial / Montana Department of Natural Resources	Harlowton AOI, Beaverhead County LiDAR Technical Data Report	Quantum Spatial	Corvallis, OR	2016	http://www.quantumspatial.com
USACE, 2010	United States Army Corps of Engineers	HEC-RAS Hydraulic Reference Manual, Version 4.1.0.	USACE Hydrologic Engineering Center	Davis, CA	2010	http://www.hec.usace.ar my.mil/software/hec-ras/
USACE, 2010	United States Army Corps of Engineers	HEC-RAS User's Manual, Version 4.1.0.	USACE Hydrologic Engineering Center	Davis, CA	2010	http://www.hec.usace.ar my.mil/software/hec-ras/
USDA, 2012, 2014	United States Department of Agriculture	National Agricultural Imagery Program (NIAP) aerial photographs.	USDA	Washington, DC	2012, 2014	http://www.fsa.usda.gov/ programs-and- services/aerial- photography/index
USGS, 1982	United States Geologic Survey	Guide for Selecting Manning's Roughness Coefficients for Natural Channels and Flood Plains, Water-supply Paper 2339.	USGS	Reston, VA	1982	http://pubs.er.usgs.gov/b rowse/usgs-publications

Table 32: Bibliography and References (continued)

Citation in this FIS	Publisher/ Issuer	Publication Title, "Article," Volume, Number, etc.	Author/Editor	Place of Publication	Publication Date/ Date of Issuance	Link
USGS, 1982	United States Geologic Survey	Interagency Advisory Committee on Water Data, Guidelines for Determining Flood Flow Frequency, Bulletin #17B of the Hydrology Subcommittee.	USGS	Reston, VA	1982	http://pubs.er.usgs.gov/b rowse/usgs-publications

